

Features

Regulated Converters

- Household, medically and ITE certified
- Class II installations (without FG)
- IP68 waterproof encapsulation
- Long life components, rugged module
- Energy Efficiency Level VI
- Cable and connector modifications on request

Description

The RACM30-ER/W series comprises reliable and highly efficient power conversion modules in a potted IP68 certified, waterproof encapsulation to fit into flush mount wall installations. All versions are covered by multiple certifications for household, medical and ITE safety standards as well. With a certified operation up to 5000m altitude and an ambient temperature range from -20°C up to +70°C, the compact modules are designed to power sanitary, healthcare, smart building, automation, and household applications. Since these modules do not require any external components, they are ready to connect and forget.

Selection Guide


| Part Number | Input Voltage Range [VAC] | Output Voltage ⁽¹⁾ [VDC] | Output Current [A] | Efficiency typ. ⁽³⁾ [%] |
|-----------------------------|---------------------------|-------------------------------------|--------------------|------------------------------------|
| RACM30-12SER ⁽²⁾ | 90-264 | 12 | 2.5 | 88 |
| RACM30-24SER ⁽²⁾ | 90-264 | 24 | 1.25 | 89.5 |

Notes:

Note1: Other output voltages on request

Note2: Efficiency is tested at nominal input (115/230VAC) and full load at +25°C ambient

Model Numbering



Notes:

Note3: Other connection types on request

RECOM
AC/DC Converter

RACM30-ER/W

30 Watt
Wired
Round Shape
Single Output





- IEC/EN60950-1 certified
- UL60950-1 certified
- ANSI/AAMI ES60601-1 certified
- IEC/EN60601-1 certified
- UL60601-1 certified
- IEC/EN60335-1 certified
- IEC/EN61558-1 certified
- IEC/EN61558-2-16 certified
- IEC/EN60601-1-2 certified
- EN55024/32 certified
- EN55014-1 (-2) certified
- IEC60529 certified

Specifications (measured @ $t_a = 25^\circ\text{C}$, nom. V_{in} (115/230VAC), full load after warm-up unless otherwise stated)

BASIC CHARACTERISTICS

| Parameter | Condition | Min. | Typ. | Max. |
|------------------------------|-------------------------------|-------|---------------|-----------------|
| Internal Input Filter | | | | Pi type |
| Input Voltage Range | | 90VAC | 230VAC | 264VAC |
| Input Current | 115VAC 230VAC | | | 1000mA 290mA |
| Inrush Current | 115VAC 230VAC | | 60A 95A | |
| No load Power Consumption | | | | 75mW |
| Input Frequency Range | | 47Hz | | 63Hz |
| Minimum Load | | 0% | | |
| Power Factor | | | 0.55 | |
| Start-up Time | 115VAC 230VAC | | 75ms 150ms | |
| Rise Time | 115VAC / 230VAC | | 10ms | |
| Hold-up Time | 115VAC 230VAC | | 15ms 55ms | |
| Internal Operating Frequency | 100% load at nominal V_{in} | | 100kHz | |
| Output Ripple and Noise | | | | 75mVp-p |

Efficiency vs. Load



REGULATIONS



| Parameter | Condition | Value |
|--------------------|-----------------------|------------------|
| Output Accuracy | | $\pm 3.0\%$ max. |
| Line Regulation | low line to high line | $\pm 1.0\%$ max. |
| Load Regulation | 0% to 100% load | $\pm 1.0\%$ max. |
| Transient Response | 100% load step change | $\pm 3.0\%$ max. |

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nom. Vin (115/230VAC), full load after warm-up unless otherwise stated)

Accuracy vs. Load

(@ min Vin to max. Vin)



PROTECTIONS

| Parameter | Type | | Value |
|-----------------------------------|---------------------------|---------------------|---|
| Input Fuse | internal (line & neutral) | | T2A, slow blow |
| Short Circuit Protection (SCP) | | | continuous, auto recovery |
| Over Voltage Protection (OVP) | 12Vout | | 17VDC, Latch OFF |
| | 24Vout | | 35VDC, Latch OFF |
| Over Voltage Category (OVC) | | | OVCII |
| Over Current Protection (OCP) | < 1 minute | 90VAC 264VAC | 140% of nominal output current, auto recovery 170% of nominal output current, auto recovery Hiccup Mode |
| Over Temperature Protection (OTP) | 95°C ambient | | thermal shutdown, auto recovery |
| Class of Equipment | | | Class II |
| Isolation Voltage ⁽³⁾ | I/P to O/P | tested for 1 minute | 4.4kVAC |
| Insulation Grade | | | reinforced |
| Leakage Current | | | 100µA max. |
| Means of Protection | 260VAC working voltage | | 2MOPP |
| Medical Device Classification | | | Type BF |

Notes:

Note3: For repeat Hi-Pot testing, reduce the time and/or the test voltage

ENVIRONMENTAL


| Parameter | Condition | | Value |
|-----------------------------|----------------------------------|-----------------------------------|--|
| Operating Temperature Range | natural convection 0.1m/s | without derating with derating | -20°C to +50°C -20°C to +70°C |
| Maximum Case Temperature | | | +85°C |
| Operating Altitude | | | 5000m |
| Operating Humidity | non-condensing | | 95% RH max. |
| IP Rating | | | IP68 |
| Pollution Degree | | | PD2 |
| MTBF | according to MIL-HDBK-217F, G.B. | +25°C +50°C | 538 x 10 ³ hours 107 x 10 ³ hours |
| Design Lifetime | E-Cap limitation | | 130 x 10 ³ hours |

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nom. V_{in} (115/230VAC), full load after warm-up unless otherwise stated)

Derating Graph

(@ Chamber and natural convection 0.1 m/s)



SAFETY AND CERTIFICATIONS

| Certificate Type (Safety) | Report / File Number | Standard |
|--|----------------------|--|
| Information Technology Equipment, General Requirements for Safety (CB Scheme) | T223-0255/17 | IEC60950-1:2005, 2nd Edition + Am2:2013 EN60950-1:2006 + A2:2013 |
| Information Technology Equipment, General Requirements for Safety | T223-0255/17 | UL60950-1, 2nd Edition:2014 CAN/CSA C22.2 No. 60950-1, 2nd Edition:2014 |
| Medical Electric Equipment, General Requirements for Safety and Essential Performance (CB Scheme) | T223-0254/17 | IEC60601-1:2005, AM1:2012 EN60601-1:2006 + A12:2014 |
| Medical Electric Equipment, General Requirements for Safety and Essential Performance | T223-0254/17 | CAN/CSA-C22.2 No. 60601-1:14, 3rd Edition 2014 ANSI/AAMI ES60601-1:2005 |
| Household and similar electrical appliances - Safety Part 1: General requirements (CB Scheme) | T211-0759/17 | IEC60335-1:2010, 5th Edition + A1:2013 EN60335-1:2012 + A11:2014 |
| Safety of power transformers, power supplies, reactors and similar products for supply voltages up to 1100V | T211-0760/17 | IEC61558-1:2005, 2nd Edition + A1:2009 EN61558-1:2005 + A1:2009 |
| Safety of transformers, reactors, power supply units and similar products for supply voltages up to 1100 V - Part 2-16: Particular requirements and tests for switch mode power supply units | | IEC61558-2-16:2009, 1st Edition + A1:2013 EN61558-2-16:2009 + A1:2013 |
| Degrees of protection provided by enclosures (IP Code) | T211-0584/17 | IEC60529-1989, 2nd-Edition+A1:1999+A2:2013 |
| RoHs 2 (2+) | | RoHs 10/10, AM2015 |

| EMC Compliance (Medical) | Condition | Standard / Criterion |
|--|---|--|
| Medical electrical equipment Part 1-2: Electromagnetic disturbances – Requirements and tests | | EN60601-1-2:2015 |
| ESD Electrostatic discharge immunity test | Air $\pm 2, 4, 8, 15\text{kV}$; Contact $\pm 8\text{kV}$ | IEC61000-4-2:2008 |
| Radiated, radio-frequency, electromagnetic field immunity test | 10V/m (80 - 2700MHz) | IEC61000-4-3:2006 + A2:2010 |
| Radiated, radio-frequency, electromagnetic field immunity test (table 9) | 27V/m (385MHz), 28V/m (450MHz), 9V/m (710, 745, 780MHz), 28V/m 1720, 1845, 1970, 2450MHz), 9V/m (5240, 5500, 5785MHz) | IEC61000-4-3:2006 + A2:2010, Criteria A |
| | 28V/m (800-960MHz) | IEC61000-4-3:2006 + A2:2010, Criteria B ⁽⁴⁾ |
| Fast Transient and Burst Immunity | AC Power Port $\pm 2.0\text{kV}$ DC Output Port $\pm 1.0\text{kV}$ | IEC61000-4-4:2012 |
| Surge Immunity | AC Power Port: L-N $\pm 0.5, 1.0\text{kV}$ | IEC61000-4-5:2005 |

Notes:

Note4: Output voltage doesn't meet specified output accuracy

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nom. V_{in} (115/230VAC), full load after warm-up unless otherwise stated)

| EMC Compliance (Medical) | Condition | Standard / Criterion |
|---|---|--|
| Immunity to conducted disturbances, induced by radio-frequency fields | AC Power Port 6V DC Output Port 6V | IEC61000-4-6:2013 |
| Power Magnetic Field Immunity | 50Hz, 60Hz, 30A/m | IEC61000-4-8:2009 |
| Voltage Dips and Interruptions | | IEC61000-4-11:2004 |
| EMC Compliance (Household) | Condition | Standard / Criterion |
| Electromagnetic compatibility of multimedia equipment – Emission Requirements | | EN55014-1:2006 + A1:2009 + A2:2011 |
| Information technology equipment - Immunity characteristics - Limits and methods of measurement | | EN55014-2:1997 + A1:2001 + A2:2008 |
| ESD Electrostatic discharge immunity test | Air $\pm 8\text{kV}$; Contact $\pm 4\text{kV}$ | EN61000-4-2:1995 + A2:2001, Criteria A |
| Radiated, radio-frequency, electromagnetic field immunity test | 3V/m (80 - 1000MHz) | EN61000-4-3:2006 + A1:2008, Criteria A |
| Fast Transient and Burst Immunity | AC Power Port: $\pm 1.0\text{kV}$ DC Power Port $\pm 0.5\text{kV}$ | EN61000-4-4:2004, Criteria A |
| Surge Immunity | AC Power Port: L-N $\pm 0.5, 1.0\text{kV}$ | EN61000-4-5:2006, Criteria A |
| Immunity to conducted disturbances, induced by radio-frequency fields | AC Power Port 3V DC Power Port 3V | EN61000-4-6:2007, Criteria A |
| Voltage Dips and Interruptions | | EN61000-4-11:2004 |
| EMC Compliance (Multimedia) | Condition | Standard / Criterion |
| Information technology equipment - Immunity characteristics - Limits and methods of measurement | | EN55024:2010 |
| ESD Electrostatic discharge immunity test | Air $\pm 2, 4, 8\text{kV}$; Contact $\pm 4\text{kV}$ | EN61000-4-2:2009, Criteria A |
| Radiated, radio-frequency, electromagnetic field immunity test | 3V/m (80 - 1000MHz) | EN61000-4-3:2006 + A2:2010, Criteria A |
| Fast Transient and Burst Immunity | AC Power Port: $\pm 1.0\text{kV}$ DC Power Port $\pm 0.5\text{kV}$ | EN61000-4-4:2004, Criteria A |
| Surge Immunity | AC Power Port: L-N $\pm 0.5, 1.0\text{kV}$ | EN61000-4-5:2006, Criteria A |
| Immunity to conducted disturbances, induced by radio-frequency fields | AC Power Port 3V DC Power Port 3V | EN61000-4-6:2009, Criteria A |
| Power Magnetic Field Immunity | 50Hz, 60Hz, 1A/m | EN61000-4-8:2010, Criteria A |
| Voltage Dips and Interruptions | | EN61000-4-11:2004, Criteria A |
| Limits of Voltage Fluctuations & Flicker | | EN61000-3-3:2013 |
| EMC Compliance (Generic Standards) | Condition | Standard / Criterion |
| Generic standards – Immunity standard for residential, commercial and light-industrial environments | | EN61000-6-1:2007 |
| Generic standards – Immunity standard for industrial environments | | EN61000-6-2:2005 |
| Generic standards – Emission standard for residential, commercial and light-industrial environments | | EN61000-6-3:2007 + A1:2011 |



DIMENSION AND PHYSICAL CHARACTERISTICS

| Parameter | Type | Value |
|---------------------------|------------------------|--|
| Material | Case Potting PCB | non-conductive black plastic, (UL94V-0) polyurethane, (UL94V-0) FR4, (UL94V-0) |
| Package Dimension (LxWxH) | | 53.0 x 378.0 x 33.5mm |
| Package Weight | | 132g max. |

continued on next page

Specifications (measured @ $t_a = 25^\circ\text{C}$, nom. V_{in} (115/230VAC), full load after warm-up unless otherwise stated)

Dimension Drawing (mm)



Wired Connection

| # | Function | Wire Color | Type |
|---|------------|------------|----------------|
| 1 | VAC in (N) | white | UL-1007, AWG20 |
| 2 | VAC in (L) | white | UL-1007, AWG20 |
| 3 | V+ | red | UL-1007, AWG22 |
| 4 | V- | black | UL-1007, AWG22 |


tc= case temperature measuring point

FC= fixing centers

Tolerance: xx.x= $\pm 0.5\text{mm}$

xx.xx= $\pm 0.25\text{mm}$

Max. tightening torque fixing screws: 0.3Nm



PACKAGING INFORMATION

| Parameter | Type | Value |
|-----------------------------|----------------|-------------------------|
| Packaging Dimension (LxWxH) | carton | 310.0 x 220.0 x 100.0mm |
| Packaging Quantity | | 10pcs |
| Storage Temperature Range | | -30°C to +80°C |
| Storage Humidity | non-condensing | 95% RH max. |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.